

Product Data Sheet



Triden Mercon V ATF

FEATURES/ BENEFITS

Triden Mercon V ATF is a multifunctional fluid for use in many brands of automatic transmissions. It meets the requirements of the Ford Motor Company specifications Mercon and Mercon V. It also meets the requirements of General Motors specification Dexron III and Chrysler's ATF+4. This lubricant provides a high level of oxidation and shear stability, resulting in cleaner transmissions and more reliable operation.

APPLICATIONS

Triden Mercon V ATF is suitable for use where the following specifications are required:

- GM Dexron III
- ATF+4
- Honda
- JASO 1A
- Mercon
- Mercon V
- Toyota SP3 and T-4

TYPICAL CHARACTERISTICS

Triden Mercon V ATF	
<i>Property</i>	
Color, Visual	Red Liquid
Viscosity, cSt @ 100°C, D-445	7.3
Brookfield Viscosity, D-2983 @ -20°C, cP @ -40°C, cP	1,500 10,000
Flash Point, °C (°F), D-92	185 (365)
Rust Test, D-665A	Pass
Copper Strip Test, D-130 3 hrs, 150°C	1b
Shear Stability, D-5273 Viscosity at 40°C, after 40 passes, cSt	6.8

Typical test data are average values only.

Minor variations that do not affect product performance are to be expected during normal manufacturing.